



SAFETY DATA SHEET DRIVELINE 75W-90 MV

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name DRIVELINE 75W-90 MV
Product number KAZ020, KAZ455, MTF759

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

Manufacturer TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

DRIVELINE 75W-90 MV

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|--|
| DISTILLATES, HYDROTREATED HEAVY PARAFFINIC <3% DMSO EXTRACT (IP 346) | 60-100% |
| CAS number: 64742-54-7 | EC number: 265-157-1 |
| | REACH registration number: 01-2119484627-25-0000 |

Classification

Asp. Tox. 1 - H304

| | |
|---|--|
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (<3% DMSO EXTRACT, IP 346) | 3-<5.0% |
| CAS number: 64742-55-8 | EC number: 265-158-7 |
| | REACH registration number: 01-2119487077-29-0000 |

Classification

Asp. Tox. 1 - H304

| | |
|---|--|
| MINERAL OIL - H304 (<3% DMSO EXTRACT, IP 346) | 3-<5.0% |
| CAS number: 64742-55-8 | EC number: 265-158-7 |
| | REACH registration number: 01-2119487077-29-0000 |

Classification

Asp. Tox. 1 - H304

| | |
|--|--|
| PHOSPHORODITHIOIC ACID, MIXED O,O-BIS (2- ETHYLHEXYL AND ISO-PR) ESTERS, ZINC SALTS | 1-<2% |
| CAS number: — | EC number: 272-723-1 |
| | REACH registration number: 01-2119493633-31-0000 |

Classification

Skin Irrit. 2 - H315
Eye Irrit. 2 - H319
Aquatic Chronic 2 - H411

| | |
|--|--|
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC. <3% DMSO EXTRACT | 1-<2% |
| CAS number: 64742-53-6 | EC number: 265-156-6 |
| | REACH registration number: 01-2119480375-34-0000 |

Classification

Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

DRIVELINE 75W-90 MV

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Get medical attention if any discomfort continues. Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. |
| Inhalation | If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. |
| Ingestion | Contact physician if larger quantity has been consumed. Rinse mouth thoroughly with water. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation. |
| Inhalation | May cause an asthma-like shortness of breath. Vapours may cause headache, fatigue, dizziness and nausea. |
| Ingestion | May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. |
| Skin contact | Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Allergic rash. |
| Eye contact | May cause temporary eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|---|
| Notes for the doctor | No specific recommendations. If in doubt, get medical attention promptly. |
|-----------------------------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|---------------------------------------|--|
| Suitable extinguishing media | Extinguish with the following media: Foam, carbon dioxide or dry powder. Use fire-extinguishing media suitable for the surrounding fire. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

5.2. Special hazards arising from the substance or mixture

| | |
|--------------------------------------|--|
| Specific hazards | Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂). No unusual fire or explosion hazards noted. |
| Hazardous combustion products | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. |

5.3. Advice for firefighters

| | |
|--|--------------------------------|
| Special protective equipment for firefighters | Leave danger zone immediately. |
|--|--------------------------------|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|---|
| Personal precautions | Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces. |
|-----------------------------|---|

DRIVELINE 75W-90 MV

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Avoid contact with skin and eyes. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

DRIVELINE 75W-90 MV

| | |
|---------------------------------------|--|
| Eye/face protection | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. |
| Hand protection | Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. |
| Other skin and body protection | Wear suitable protective clothing as protection against splashing or contamination. |
| Hygiene measures | Wash contaminated clothing before reuse. Wash promptly with soap and water if skin becomes contaminated. |
| Respiratory protection | No specific recommendations. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-------------------------------|
| Appearance | Clear liquid. |
| Colour | Brown. |
| Odour | Oil-like. |
| pH | Scientifically unjustified. |
| Melting point | Not determined. |
| Initial boiling point and range | >250°C @ |
| Flash point | 220°C |
| Evaporation rate | Not determined. |
| Upper/lower flammability or explosive limits | Not determined. |
| Vapour pressure | Not determined. |
| Vapour density | Not determined. |
| Relative density | 0.884g/cm ³ @ 15°C |
| Solubility(ies) | Insoluble in water. |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | 95 cSt @ 40°C |

9.2. Other information

| | |
|--------------------------|-------|
| Other information | None. |
|--------------------------|-------|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|---|
| Reactivity | There are no known reactivity hazards associated with this product. |
|-------------------|---|

10.2. Chemical stability

DRIVELINE 75W-90 MV

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Petroleum Distillates (Solvents Neutral)

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards This chemical can be hazardous when inhaled and/or touched.

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish

Petroleum Distillates (Solvents Neutral)
LC₅₀, 96 hours: >100 mg/l mg/l, Fish

Acute toxicity - aquatic invertebrates

Petroleum Distillates (Solvents Neutral)
EC₅₀, 48 hours: >100 mg/l mg/l, Daphnia magna

Acute toxicity - aquatic plants

Petroleum Distillates (Solvents Neutral)
IC₅₀, 72 hours: >100 mg/l mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The product is moderately biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

DRIVELINE 75W-90 MV

12.4. Mobility in soil

Mobility The product is insoluble in water.

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

DRIVELINE 75W-90 MV

| | |
|-----------------------------|--|
| National regulations | EH40/2005 Workplace exposure limits. |
| EU legislation | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

| | |
|----------------------------------|--|
| Revision comments | NOTE: Lines within the margin indicate significant changes from the previous revision. |
| Issued by | Health & Safety Department |
| Revision date | 14/01/2020 |
| Revision | 1 |
| Supersedes date | 09/03/2017 |
| SDS number | 32288 |
| SDS status | Approved. |
| Hazard statements in full | H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. |